

# TECALAN – medium pressure hose

## Type DKG-C

Textile reinforced rubber hose, metal braiding outside, according DIN 73379 Type C as feed pipe for technical fluids.

Abrasion resistant and flexible · suitable for gasoline, diesel, most hydraulic fluids, lubricants, coolant and waterbased liquids · Temperature range: -30°F up to +195°F continuous service (short time up to +230°F)



code: TECALAN- hose	inside- Ø inch	outside- Ø mm	wall- thickness in mm	pressure rates in psi			min. bending radius in mm	weight kg/100 m	part no.
				service	test	burst			
DKG - C 3	3/16"	10,5	3,0	435	650	1.300	35	12,7	0201010194
DKG - C 4	7/32"	11,5	3,0	435	650	1.300	40	13,4	0201010195
DKG - C 6	19/64"	13,5	3,0	435	650	1.300	50	17,6	0201010196
DKG - C 8	23/64"	15,0	3,0	360	545	1.090	60	19,0	0201010197
DKG - C 10	29/64"	18,5	3,5	360	545	1.090	80	33,0	0201010198
DKG - C 13	35/64"	23,0	4,5	360	545	1.090	90	38,0	0201010100

Assembly with TECALAN press-couplings is standard in general.

**Construction / Material:** inner tube synthetic NBR rubber reinforced by vulcanized textile layer, metal braiding outside.