

TECALAN – medium pressure hose

Type DKG-S

Rubber hose with metal braiding outside, according DIN EN ISO 6806, as feed pipe for technical fluids.

Abrasion resistant and flexible · suitable for fuel oil, diesel*, most hydraulic fluids, coolant and water-based liquids · Temperature range: -30°F to +195°F



code: TECALAN- hose	Inside- Ø inch	outside-Ø mm	wall- thickness in mm	pressure rates in psi			min. bending radius in mm	weight kg/100 m	part no.
				service	test	burst			
DKG - S 03	3/16"	9,0	2,25	290	435	870	25	10,8	0201020253
DKG - S 04	1/4"	10,5	2,5	290	435	870	30	13,5	0201020254
DKG - S 06	19/64"	12,5	2,5	217	325	650	40	17,3	0201020255
DKG - S 08	23/64"	14,5	2,5	217	325	650	60	19,7	0201020256
DKG - S 10	1/2"	17,5	3,0	145	217	435	80	25,3	0201020257
DKG - S 13	39/64"	22,0	3,35	217	325	650	100	42,1	0201020258
DKG - S 16	43/64"	26,0	4,5	145	217	435	150	55,8	0201020259

Assembly with TECALAN press-couplings is standard in general.

Construction / Material: inner tube synthetic NBR rubber, outside layer metal braiding. *RME additive up to 12%.